# **Dynafine<sup>®</sup> Detail Sander**

- · Amazingly smooth and very quiet. Lightweight... only 1.6 lbs!
- Uses reattachable and PSA mounted, coated non-woven nylon and sponge abrasives, see page 56.
- 15,000 RPM rear exhaust air motor. Features 1/32" dia. orbital action for a superior finish.
- Insulated composite handle is offset for operator comfort and may be adjusted for left or right-handed users.
- Non-marring composite Dynaswivel<sup>®</sup> flow-control speed regulator is included.
- · Many versatile applications:
- Composite bumper repair; bevel edges of cut-outs; restoration work.
- Grooves, contours, window sills, doorjambs, spoilers and more!

## Model 10800

• Includes tear-drop hook-face pads.

## **10810 Versatility Kit**

 Includes tool with hook-face and PSA pads and an assortment of coated hook-face, non-woven nylon and sponge abrasives, (see page 56 for abrasives).

# **Dynafine**<sup>®</sup> **Finger Sander**

### Model 10820

- Tiny 1/32" diameter orbital action for fine finishes. Eliminate tedious hand sanding.
- Lightweight... only 1.6 lbs. Excellent for use on edges, corners and hard-to-reach areas. Eliminate wrapping sand paper around paint sticks, let the tool do the work.
- Includes tool with 3/8" wide sanding arm, sample platen pads and sample abrasive strips (120, 180 and 240 grit).

### **10821 Deluxe Versatility Kit**

- 10820 tool, 57932 and 57931 3/4" Sanding Arms.
- Hook-face and PSA pads.
- 3/8" and 3/4" abrasive strip assortment (120, 180, 240 grits).
- Coated hook-face, non-woven nylon and sponge abrasives (see page 56 for abrasives).









Model	Motor	Motor	Sound	Air Flow Rate	Hose	Air Pressure	Weight	Length	Height
Number	hp	RPM	Level	CFM/SCFM	Size	PSIG	Pound	Inch	Inch
All Models	.16	15,000	65 dB(A)	2/19	3/8"	90	1.6	9	3-3/4